

Technical Data PILOT TEST

PILOT TEST SPECIFICATIONS

Test Signal	Speech
Hearing Level Range	70, 60, 50, 40, 35, 30, 25 dB HL
Speech Signal Source	Wave files

PURE TONE SCREENING

Test Signals	Pure tone (steady and pulse)
Test Frequencies	125, 250, 500, 750, 1000, 1500, 2000, 3000, 4000, 6000, 8000 Hz
Level Steps	5 dB
Hearing Level Range AC	-10 dB HL to 100 dB HL

DEVICE GENERAL

Dimensions	W x D x H: 30.5 cm x 26 cm x 6.5 cm
Weight	1.3 kg
Power Supply	100 - 240 V~, 50/60 Hz, app. 15 VA
Display	10.9 cm x 5.8 cm LED color display
Language	English, French, German, Spanish
PC Interface (optional)	USB

PRINTER OPTIONAL

Type	HM-E300, 3" thermal printer
Printing Time	<5 seconds per test result
Power Supply	USB
Dimensions	W x D x H: 10.5 cm x 14 cm x 6 cm
Weight	475.8 g (without paper roll)

STANDARDS

Audiometer	IEC 60645-1, Type 4
Safety	IEC/EN 60601-1, Class I, Type B applied parts
EMC	IEC 60601-1-2
CE 0123	Class IIa according to Medical Device Regulation (EU) 2017/745

AVAILABLE LANGUAGES FOR SPEECH TEST

Standard	Arabic, Chinese, Croatian, English, French, German, Greek, Italian, Polish, Russian, Serbian, Spanish, Swiss German, Turkish, Vietnamese
Optional	Afrikaans, Basque, Catalan, Czech, Danish, Dutch, Finnish, Galician Hungarian, Japanese, Korean, Norwegian, Polish Audiofon, Portuguese, Romanian, Slovakian, South Sotho, Swedish, Xhosa, Zulu

Specifications are subject to change without notice.