MedRx®

www.medrx-diagnostics.com

HID (plug & play)

Video Otoscope

USB Powered

Store Images in Noah, retrieve results easily for follow-up visits showing the patients their progress

Ideal Design for Cerumen Management and Probe Tube Placement.

Video Otoscope

Technical Specs

Model NO: U42M
Image Sensor: 1/10” High Color Sensor
Camera diameter: 4.2mm
Pixel Size: 2.25µm x 2.25µm
Specula: Heine 4mm
Resolution: 1280 (H) x 720 (V)
AGC: Auto
AES: Auto
AWB: Auto
Dynamic Range: 68dB
S/N Ratio: 37dB
Lens Construction: 1G +2P + IR
Lens F/NO: F3.8
Depth of Field: 10mm – 30mm
Light Source: 6pcs High Luminous White Color LED
Power Input: DC 3.6 ~ 5V
Output System: USB Output
Power Consumption: 0.5W
Operating Temperature: -10°C To +35°C
Operating Humidity: 30%~90%Rh
TV Distortion: < 5%

Otoscope Features

- Capture, View and Store Clear Still Images and Live Video Recordings
- Perform an Otoscopic Examination
- View the Probe Microphone Tube in the Ear Canal
- Conveniently Shows a List of Captured Pictures, Comments and Previews of the Selected Images
- An Integrated Video Module is Available in MedRx Software
- Ideal for Cerumen Management
- PC-based via USB Connection
- HID device - True Plug and Play
- Noah, TIMS, Blueprint OMS and Sycle Compatible

MedRx Minimum Computer Specs:
Windows® PC compatible computer, Intel™ i5, 2.0 GHz or better. 4 GB RAM. 20 GB free hard drive space. Available 2.0 USB Port. Windows 10 or 11 Professional, Compatible with 3.0 USB.

MedRx®
Good Things Come in Small Packages

MedRx International
DGS Diagnostics Sp. z o.o.
Rosówek 43
72-001 Kołbaskowo, Poland
Phone: +48 91 835 63 00
Email: orders@medrx-diagnostics.com
www.medrx-diagnostics.com

Distributed by:

View the Probe Microphone Tube in the Ear Canal.